

Reolink TrackMix LTE

4G LTE Dual-Lens Camera with Auto-Zoom Tracking

- Dual-View Display
- Auto-Zoom Tracking
- 4G LTE Network

Specifications

| Video & Audio | |
|-----------------------|---|
| Image Sensor | 1/3"CMOS Sensor |
| Video Resolution | Up to 3840×2160 (8.0 Megapixels) at 15 frames/sec |
| Lens | f=2.8mm@F=1.6 , f=8mm@F=1.6 |
| Video Compression | H.264,H.265 |
| Field of View | • Horizontal: 108.4°-38° • Vertical: 57.3°-21.2° |
| Zoom Mode | 6X hybrid zoom |
| Day & Night | IR-cut filter with auto-switching |
| Infrared Night Vision | Up to 30 Meters (100ft)(LED: 2pcs/ 850nm) |
| Color Night Vision | Spotlight: 1pcs/6500K/450 Lumens |
| Audio | Two-way audio |
| Power | |
| Battery | 7.2V 5100mAh rechargeable battery (Battery life varies based on settings, usage & temperature) 36.72Wh(Power capacity) |

| | |
|--------------------------|---|
| Solar | Reolink Solar Panel 2 |
| DC Power | 5V/2A |
| Interface | |
| Power | USB Type-C port |
| System | Reset button |
| Storage | Micro SD card slot (max. 128GB) |
| Audio | Built-in microphone and speaker |
| Pan & Tilt | |
| Pan &Tilt | Pan: 355°, Tilt: 0°~90°; (Speed can be set) |
| Preset Points | 32 |
| Auto Tracking | Support |
| 3G/4G Bandwidth | |
| Frequency Bands | Europe version: LTE FDD: B1/B3/B7/B8/ B20/B28A WCDMA: B1/B8 USA version: LTE FDD: B2/B4/B5/B12/ B13/B14/B66/B71 WCDMA: B2/B4/B5 Australia version: LTE FDD: B1/B3/B5/ B7/B8/B28 LTE-TDD: B40 WCDMA: B1/ B5/B8 |
| Transmission Data | LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL) LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL) HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL) UMTS: Max 384Kbps(DL), Max 384Kbps(UL) |
| Software Features | |
| Frame Rate | <ul style="list-style-type: none"> • Mainstream: 10fps - 15fps • Substream: 10fps - 15fps |
| Code Rate | <ul style="list-style-type: none"> • Mainstream: 1024Kbps -4096Kbps • Substream: 64Kbps -512Kbps |
| OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| Smart Alarm | PIR detection/person detection/ vehicle detection/pet detection |

| | |
|----------------------------|---|
| Record Mode | Motion-triggered recording |
| Protocols & Standards | SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P |
| Maximum User Access | Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) |
| Work with | Google Assistant, Reolink Cloud |
| Working Environment | |
| Operating Temperature | -10°C~+55°C (14°F~131°F) |
| Operating Humidity | 20% ~ 85% |
| Weatherproof | IP65 |
| Size & Weight | |
| Dimensions | 228.2*147*129mm |
| Weight | 1.4KG |
| Warranty | |
| Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Gallery & Specs



1. Spotlight
2. Infrared LED
3. Lens
4. Mic
5. Daylight Sensor
6. PIR Sensor



1. Micro SD Card Slot

