



020-1250 through 020-1256

Arc Flash Construction Harness : DE 3D, DE QC Chest, DE FD, DE QC Legs

FEATURES :

- Dorsal D-ring
- Front D-ring
- Side D-rings
- Quick-connect chest
- Mating buckle torso adjusters
- Quick-connect legs
- Shoulder pad
- Fixed waist pad with quick-connect belt
- Fixed leg pads
- 40 Cal rated aramid webbing

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 5.7 lbs. (2.6 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140
ASTM	F887

SIZE(S)	
020-1250	X-Small
020-1251	Small
020-1252	Medium
020-1253	Large
020-1254	X-Large
020-1255	2X
020-1256	3X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Aramid
D-ring(s)	Dielectric coated steel
Adjuster buckles	Dielectric coated steel
Chest connection	Dielectric coated steel
Leg connection	Dielectric coated steel
Pads	Nomex ®
Belt	Aramid; Dielectric coated steel