



## 020-1344 through 020-1350

### Arc Flash Construction Harness : DE 3D, DE QC Chest, TB Legs

#### FEATURES :

- Dorsal D-ring
- Side D-rings
- Mating buckle chest
- Friction buckle torso adjusters
- Tongue buckle legs
- Component backers
- Shoulder pad
- Fixed waist pad with tongue-buckle belt
- Fixed leg pads
- 40 Cal rated aramid webbing

#### FALL ARREST POINT(S) :

- 1 dorsal D-ring

#### ITEM WEIGHT :

- 5.6 lbs. (2.5 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140
ASTM	F887

SIZE(S)	
020-1344	X-Small
020-1345	Small
020-1346	Medium
020-1347	Large
020-1348	X-Large
020-1349	2X
020-1350	3X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Aramid
D-ring(s)	Zinc-plated steel
Adjuster buckles	Zinc-plated steel
Chest connection	Zinc-plated steel
Leg connection	Steel tongue buckle w/ SS grommets
Component backers	NB synthetic; FR treated poly; NBR rubber
Pads	Nomex ®
Belt	Aramid; Steel; Stainless steel