



Latitude HD 7' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- Durable housing and premium webbing increase strength and longevity.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.

Class

1

Anchor at or above dorsal D-ring



Product shown:
FS-FSP14075-W

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 29 in. (74 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 11 in. (1.8 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	36 in. (91 cm)
Use below d-ring	3 ft. (0.91 m)
Min. required fall clearance	8 ft. 1 in. (2.5 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	25mm UHMPE webbing
Housing	Aluminum
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



SAFEWAZE

TECHNICAL DATA SHEET

Latitude HD 7' Web SRL-P

LATITUDE

HD

Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

Part Number	Single Leg (S) / Dual Leg (D)		Working Length (ft.)		Lifetime Material	Lifetime Dimensions (in.)	Housing Material	CONNECTOR												ATTACHMENT											
								U Steel Snap Hook ①	Steel Snap Hook ②	AlU Snap Hook ③	Dielectric Snap Hook ④	Steel Tie Back Hook ⑤	U Steel Swivel Snap Hook ⑥	Steel Swivel Snap Hook ⑦	Steel Swivel Rebar Hook ⑧	AlU Rebar Hook ⑨	AlU Captive Eye Carabiner ⑩	AlU Swivel Carabiner ⑪	No Attachment Steel Carabiner ⑫	Tip Lock Steel Carabiner ⑬	AlU Captive Eye Carabiner ⑭	AlU Carabiner ⑮	AlU Snap Hook ⑯	FS-ES13 ⑰	Cable Mount Bracket ⑱	Soft Loop ⑲	Integrated BWR ⑳	104 BWR ㉑	9012 BWR ㉒	9013 BWR ㉓	
TH40079-FS007W	1	S	7	UHMPE webbing	1X.05	Aluminum	3.3	X																							
FS-FSP1407-W	1	S	7	UHMPE webbing	1X.05	Aluminum	3.4	X											X												
FS-FSP1407-W-RBH	1	S	7	UHMPE webbing	1X.05	Aluminum	4.4							X				X													
FS-FSP1407-W-TBH	1	S	7	UHMPE webbing	1X.05	Aluminum	3.4						X					X													
FS-FSP14075-W	1	D	7	UHMPE webbing	1X.05	Aluminum	6.8	X										X													
FS-FSP14085-W-RBH	1	D	7	UHMPE webbing	1X.05	Aluminum	8.8						X					X						X							
FS-FSP14085-W-GCC	1	D	7	UHMPE webbing	1X.05	Aluminum	8.8									X		X						X							
FS-FSP15075-W-BWB	1	D	7	UHMPE webbing	1X.05	Aluminum	6.1	X																			X				
FS-FSP15085-RBH-BWB	1	D	7	UHMPE webbing	1X.05	Aluminum	8.1						X													X					
FS-FSP14075-W-TBH	1	D	7	UHMPE webbing	1X.05	Aluminum	4.4					X						X						X							
023-5369	1	D	7	UHMPE webbing	1X.05	Aluminum	5.9	X																			X				
023-5370	1	D	7	UHMPE webbing	1X.05	Aluminum	7.9							X													X				
FS-FSP1409-W	1	S	9	UHMPE webbing	1X.05	Aluminum	3.6	X										X													
FS-FSP1409-W-RBH	1	S	9	UHMPE webbing	1X.05	Aluminum	4.6						X					X													
020-5270	1	S	9	UHMPE webbing	1X.05	Aluminum	3.1			X										X											
FS-FSP1409-W-DL	1	D	9	UHMPE webbing	1X.05	Aluminum	7.2	X										X													
FS-FSP1409-W-DL-RBH	1	D	9	UHMPE webbing	1X.05	Aluminum	9.2							X				X								X					
FS-FSP1409-W-DL-BWB	1	D	9	UHMPE webbing	1X.05	Aluminum	6.5	X																			X				
FS-FSP1409WDLRBHALU	1	D	9	UHMPE webbing	1X.05	Aluminum	8.5										X										X				
FS-FSP1409WDLRBH-BWB	1	D	9	UHMPE webbing	1X.05	Aluminum	9.3							X													X				
SW8008-10	1	S	10	Steel Cable	Ø3/16	Polymer	5.1	X										X													
SW8008-10-ALU	1	S	10	Steel Cable	Ø3/16	Polymer	4.9			X								X													
SW8008-10-RBH	1	S	10	Steel Cable	Ø3/16	Polymer	6.1				X				X			X													
SW8008-10-ALU-RBH	1	S	10	Steel Cable	Ø3/16	Polymer	5.7										X		X												
SW8008-10-DL	1	D	10	Steel Cable	Ø3/16	Polymer	9.3	X																			X				
SW8008-10-ALU-DL	1	D	10	Steel Cable	Ø3/16	Polymer	8.9			X																	X				
SW8008-10-RBH-DL	1	D	10	Steel Cable	Ø3/16	Polymer	11.3						X														X				
SW8008-10-ALU-RBHDL	1	D	10	Steel Cable	Ø3/16	Polymer	10.5										X										X				
FS-FSP1211-G	1	S	11	Steel Cable	Ø3/16	Polymer	6.2		X									X													
FS-FSP1211-SS	1	S	11	S.S Cable	Ø3/16	Polymer	6.2		X									X													
FS-FSP1211-G-RBH	1	S	11	Steel Cable	Ø3/16	Polymer	7.2								X			X													
FS-FSP14095-W	1	D	11	UHMPE webbing	1X.05	Aluminum	8.4	X										X							X						
FS-FSP14095-W-BWB	1	D	11	UHMPE webbing	1X.05	Aluminum	8.4	X																			X				
FS-FSP14095-W-RBH	1	D	11	UHMPE webbing	1X.05	Aluminum	10.4							X				X							X						
021-5276	1	S	11	UHMPE webbing	1X.05	Aluminum	4.2									X		X													
021-5286	1	S	11	UHMPE webbing	1X.05	Aluminum	3.7			X										X											
021-5287	1	S	11	UHMPE webbing	1X.05	Aluminum	4.5										X				X										
FS-2011N	1	S	11	UHMPE webbing	1X.05	Aluminum	3.6	X										X													
FS-FSP1411-W	1	S	11	UHMPE webbing	1X.05	Aluminum	4.2	X										X													
FS-FSP1411-W-RBH	1	S	11	UHMPE webbing	1X.05	Aluminum	5.2						X					X													
FS-FSP1411-W-TBH	1	S	11	UHMPE webbing	1X.05	Aluminum	5.2						X					X													





Dispositivo autorretráctil SRL-P Latitude HD 7' Web

*Consulte la tabla para ver los números de pieza, las configuraciones de los ganchos y los pesos de los productos

CARACTERÍSTICAS:

- Sistema de freno interno confiable que elimina la necesidad de un cabo de vida externo
- Carcasa duradera y tejido premium que aumenta la fuerza y la vida útil
- Punto de enganche 360/180° que ofrece un rango de movimiento completo
- Disponibles para una pierna o para ambas piernas
- Compatibilidad con varios tipos de gancho (consultar tabla)
- Todos los componentes cumplen con las pautas de Z359.12

Clase

1

Anclaje al mismo nivel o por encima de la argolla en D dorsal



Producto expuesto:
FS-FSP14075-W

CAPACIDAD DE PESO DEL USUARIO

ANSI	de 130 a 310 lb (de 59 a 140.6 kg)
OSHA	Hasta 420 lb (190.5 kg)

ANSI CLASE 1 (SOBRE LA ARGOLLA EN D)

Fuerza máxima de amortiguación	≤ 1,800 lb (816.5 kg)
Fuerza promedio de amortiguación	≤ 1,350 lb (612.4 kg)
Distancia máxima de amortiguación	≤ 42 in (107 cm)
Distancia real de amortiguación	≤ 29 in (74 cm)
Distancia máxima de caída libre	24 in (61 cm)
Uso debajo de la argolla en D	prohibido
Distancia de caída mínima requerida	5 ft 11 in (1.8 m)
Consulte el manual de instrucciones del usuario para ver todos los requisitos de espacio.	

NORMAS CUMPLIDAS

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

OSHA (POR DEBAJO DE LA ARGOLLA EN D)

Fuerza máxima de amortiguación	≤ 1,800 lb (816.5 kg)
Fuerza promedio de amortiguación	≤ 900 lb (408.2 kg)
Distancia máxima de amortiguación	N/C
Distancia real de amortiguación	≤ 19 in (48 cm)
Distancia máxima de caída libre	36 in (91 cm)
Uso debajo de la argolla en D	3 ft (0.91 m)
Distancia de caída mínima requerida	8 ft 1 in (2.5 m)
Consulte el manual de instrucciones del usuario para ver todos los requisitos de espacio.	

ESPECIFICACIÓN DEL MATERIAL

Tejido	Tejido UHMPE de 25 mm
Carcasa	Aluminio
Soporte	Acero, aluminio (según la configuración)
Opciones de gancho	Acero, aluminio, dieléctrico (según la configuración)



Dispositivo autorretráctil SRL-P Latitude HD 7' Web

LATITUDE
HP

Capacidad: ANSI entre 130 y 310 lb (entre 59 y 141 kg)
OSHA hasta 420 lb (191 kg)

Figure 1 shows 22 types of climbing equipment, numbered 1 through 22. The items are arranged in two rows. The first row contains items 1 through 12, and the second row contains items 13 through 22. The equipment includes various types of carabiners, connectors, and specialized climbing hardware.