## PRODUCT ID: 25937

Outdoor Blank-out LED Backlit Sign

### **MODEL**

PHX1418G-120/120-277VAC



#### **DIMENSIONS**

14" H x 18" W x 2.5" D (est. 7.151 lbs)

### **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

### **CONSTRUCTION**

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface Mounting Channel: None

### **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC UL/cUL Listed: Listed for wet locations

### **MESSAGE**

Color: Black opaque

Font: Swiss 721 Bold BT
Illumination: Backlit with high intensity LEDs. Message blanks out when off
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	<b>AMPS</b>
ATM ONLY	Green Wide Angle LED	3.75"	0.368-0.159

NOTE: Above messages are independently controlled.

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

