

PRODUCT ID: 32152

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1418GR-F942/120-277VAC



DIMENSIONS

14" H x 18" W x 2.5" D (est. 6.288 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE

LED/COLOR


HEIGHT

AMPS

FAN ON - SAFE TO ENTER	Green Wide Angle LED	1.5"	0.195-0.084
DO NOT ENTER	Red Wide Angle LED	1.5"	0.131-0.057

NOTE: Above messages are independently controlled.

Sample Display Options



Frame Detail

