Product View PRODUCT ID: 35325 NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. Outdoor Blank-out LED Direct-view Sign MODEL TCL77W-224H/12-24VDC DIMENSIONS 7" H x 7" W x 2.5" D (est. 3.275 lbs) CLASS CLASS: TCL Series Control Method: Switch (not included) or external relay. CONSTRUCTION Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: Injection molded, impact resistant Lexan hood with Lexan lenses Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None - 3 in · **ELECTRICAL** Flashing: Factory setting 55fpm. Input Voltage: 12-24 VDC Photodimming: None UL/cUL Listed: Listed for wet locations MESSAGE Illumination: Super bright direct view LEDs. Message blanks out when off. 7 in Sign Messages: See message table below MESSAGE LED/COLOR |HEIGHT | AMPS White Indicator Dot White Wide Angle LED 4.0" 0.533-0.267 White Indicator Dot (Flashing) White Wide Angle LED 0.533-0.267 4.0" r⊴-----2 1/2 in -----⊳ 7 in Frame Detail NOTE: Above messages are independently controlled.