

PRODUCT ID: 38670

Indoor Blank-out LED Backlit Sign

MODEL

SBL1212R-A268/120-277VAC



DIMENSIONS

12" H x 12" W x 2.5" D (est. 7.186 lbs)

CLASS

Class: SBL Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed

MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.


Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail



MESSAGE

LED/COLOR

HEIGHT

AMPS

MESSAGE	LED/COLOR	HEIGHT	AMPS
TEST IN PROGRESS DO NOT ENTER	Red Wide Angle LED	1.375", 1.4375"	0.065-0.028

NOTE: Above messages are independently controlled.