

PRODUCT ID: 40485

Outdoor LED Backlit Sign

MODEL

PHXF1434B-125/120-277VAC



DIMENSIONS

14" H x 34" W x 2.5" D (est. 9.179 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Refer to message table (PMS 300 Blue)

Font: Other: (New Century Schoolbook Bold)

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below


MESSAGE	LED/COLOR	HEIGHT	AMPS
---------	-----------	--------	------

ATM	White Wide Angle LED	8.0"	0.672-0.291
-----	----------------------	------	-------------

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

