

# PRODUCT ID: 41414

## Outdoor Blank-out LED Backlit Sign

### MODEL

PHX1434GG-K551/120-277VAC



### DIMENSIONS

14" H x 34" W x 2.5" D (est. 11.495 lbs)

### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

### MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off



Sign Messages: See message table below

## Product View


NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



### Sample Display Options



### Frame Detail



MESSAGE	LED/COLOR	HEIGHT	AMPS
ADDITIONAL PARKING	Green Wide Angle LED	2.75"	0.347-0.150
Left Arrow	Green Wide Angle LED	3.0"	0.347-0.150

NOTE: Above messages are independently controlled.