

## PRODUCT ID: 42276

### Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX1442WGR-L050/120-277VAC



#### DIMENSIONS

14" H x 42" W x 2.5" D (est. 14.697 lbs)

#### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

#### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

#### MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
CURRENCY EXCHANGE	White Wide Angle LED	3.75"	0.412-0.178
OPEN	Green Wide Angle LED	3.75"	0.217-0.094
CLOSED	Red Wide Angle LED	3.75"	0.144-0.062

NOTE: Above messages are independently controlled.

### Sample Display Options



### Frame Detail

