

PRODUCT ID: 46210
LED Panel Sign

MODEL
LPS7716DRR-L935/120-277VAC



DIMENSIONS
77" H x 16" W x 7.5" D (est. 133.978 lbs)

CLASS
Class: LPS Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Back Construction: 0.125" Aluminum sheet
Cabinet: Mitered extruded aluminum frame with 2 hinged faces. LED displays installed with sign-in-sign construction. Moisture absorbent interior coating
Face Material: 1/8" thick routed aluminum panel.
Faces: Double Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface
Number of Displays: (16)

ELECTRICAL
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE
Color: Black opaque
Font: Swiss 721 Bold Condensed BT
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
BREAK OUT	Red Wide Angle LED	1.75"	0.087-0.038
A/B ACCUM FULL	Red Wide Angle LED	1.75"	0.087-0.038
C/D ACCUM FULL	Red Wide Angle LED	1.75"	0.087-0.038
SCRAPER OFF	Red Wide Angle LED	1.75"	0.087-0.038
SCRAPER LOW	Red Wide Angle LED	1.75"	0.087-0.038
CHILL ROLL LIMIT	Red Wide Angle LED	1.75"	0.087-0.038
CALENDER OPEN	Red Wide Angle LED	1.75"	0.087-0.038
BINDER TRAY LEVEL	Red Wide Angle LED	1.75"	0.087-0.038

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

