

PRODUCT ID: 48263

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1818GG-M370/12-24VDC



DIMENSIONS

18" H x 18" W x 2.5" D (est. 55009.998 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 12-24 VDC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE

LED/COLOR

HEIGHT

AMPS

PUBLIX PARKING LEVEL 2	Green Wide Angle LED	2.5"	2.813-1.407
AND LEVEL 3	Green Wide Angle LED	2.5"	1.947-0.973

NOTE: Above messages are independently controlled.

Sample Display Options



Frame Detail

