

PRODUCT ID: 52870
Outdoor LED Backlit Sign

MODEL
PHXF1418W-N382K/120-277VAC

DIMENSIONS
14" H x 18" W x 2.5" D (est. 7.52 lbs)



CLASS
CLASS: PHXF Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" thick, impact modified acrylic (0000)
Faces: Single Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface
Mounting Channel: None

ELECTRICAL
Flashing: Not Included
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE
Color: Refer to message table (Yellow Translucent (R255 G242 B0), Black Opaque)
Font: Swiss 721 Bold BT
Illumination: White high intensity LED backlit. Message always visible.
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
PEDESTRIAN CROSSING PROCEED SLOWLY	Yellow Translucent, Black Opaque, White Wide Angle LED	1.875"	0.368-0.159

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

