

PRODUCT ID: 52957

Outdoor LED Backlit Sign

MODEL

PHXF1016W-193R/120-277VAC



DIMENSIONS

10" H x 16" W x 2.5" D (est. 6.275 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Red translucent

Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.


Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail



MESSAGE	LED/COLOR	HEIGHT	AMPS
LASER IN USE	Red Translucent, White Wide Angle LED	2.125"	0.239-0.103

NOTE: Above messages are independently controlled.