

PRODUCT ID: 55762
Outdoor Blank-out LED Backlit Sign

MODEL
PHX1442AGRGGR-528/120-277VAC



DIMENSIONS
14" H x 42" W x 2.5" D (est. 14.697 lbs)

CLASS
Class: PHX Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION
Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" thick, dark grey diffused acrylic
Faces: Single Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface
Mounting Channel: None

ELECTRICAL
Flashing: Not Included
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations


MESSAGE
Color: Black opaque
Font: Swiss 721 Bold BT
Illumination: Backlit with high intensity LEDs. Message blanks out when off
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
ATM	Amber Wide Angle LED	3.25"	0.116-0.050
OPEN	Green Wide Angle LED	3.25"	0.131-0.057
CLOSED	Red Wide Angle LED	3.25"	0.087-0.038
DRIVE-UP	Green Wide Angle LED	3.0"	0.173-0.075
OPEN	Green Wide Angle LED	3.25"	0.131-0.057
CLOSED	Red Wide Angle LED	3.25"	0.087-0.038


NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

