

PRODUCT ID: 58324

Outdoor LED Backlit Sign

MODEL

PHXF1218W-O878R/120-277VAC

DIMENSIONS

12" H x 18" W x 2.5" D (est. 7.559 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Red translucent

Font: Swiss 721 Bold Condensed BT


Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below




Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail



MESSAGE

LED/COLOR

HEIGHT

AMPS

EV CHARGING ONLY w/ Tow symbol and EV Symbol	Red Translucent, White Wide Angle LED	1.5", 2.75", 9.25"	0.304-0.132
--	---------------------------------------	--------------------	-------------

NOTE: Above messages are independently controlled.