

PRODUCT ID: 58351

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1224G-E844/120-277VAC



DIMENSIONS

12" H x 24" W x 2.5" D (est. 10.483 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold Condensed BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

| MESSAGE | LED/COLOR | HEIGHT | AMPS |
|-----------------|----------------------|--------|-------------|
| DRIVE-THRU OPEN | Green Wide Angle LED | 3.25" | 0.412-0.178 |

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

