

PRODUCT ID: 59016

Outdoor Blank-out LED Backlit Sign

MODEL

S-PHX1434GRG-P074/120-277VAC



DIMENSIONS

14" H x 34" W x 2.5" D (est. 14.458 lbs)

CLASS

Class: PHX Smart Sign Series

Control Method: Sign Control Software

Communications (by others): Ethernet connection and static IP lease required
Control: DHCP enabled network and server grade computer running Windows 7 or Windows Server 2008 or higher

CONSTRUCTION

Back Construction: 0.050" Extended Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
Teller w/ Teller Symbol	Green Wide Angle LED	3.5", 5.0"	0.347-0.150
Teller w/ Teller Symbol	Red Wide Angle LED	3.5", 5.0"	0.231-0.100
Night Depository	Green Wide Angle LED	3.0"	0.347-0.150

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options



Frame Detail

