

PRODUCT ID: 59764

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1818GR-100/120-277VAC



DIMENSIONS

18" H x 18" W x 2.5" D (est. 13.843 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Product View


NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
OPEN w/ Right Arrow	Green Wide Angle LED	4.0", 3.0"	0.281-0.122
CLOSED	Red Wide Angle LED	4.0"	0.131-0.057

NOTE: Above messages are independently controlled.

Sample Display Options



Frame Detail

