

# PRODUCT ID: 61885

## Outdoor Blank-out LED Backlit Sign

### MODEL

PHX1018AR-P881/120-277VAC



### DIMENSIONS

10" H x 18" W x 2.5" D (est. 8.385 lbs)

### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

### MESSAGE

Color: Black opaque

Font: Swiss 721 Bold Condensed BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
PIT LOW LEVEL	Amber Wide Angle LED	2.0"	0.087-0.038
OVERFLOW	Red Wide Angle LED	2.0"	0.087-0.038

NOTE: Above messages are independently controlled.

### Sample Display Options



### Frame Detail

