

PRODUCT ID: 62033

Outdoor Blank-out LED Backlit Sign

MODEL

PHX811W-P931O/120-277VAC



DIMENSIONS

8" H x 11" W x 2.5" D (est. 4.168 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Refer to message table (Orange Translucent, Black Blockout)


Font: Swiss 721 Bold Condensed BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE

LED/COLOR

HEIGHT

AMPS

MESSAGE	LED/COLOR	HEIGHT	AMPS
GO SLOW PEDESTRIAN CROSSING w/ Pedestrian Crosswalk	Printed Orange Translucent, White Wide Angle LED	1.75", 1.0", 3.75"	0.131-0.057

NOTE: Above messages are independently controlled.