

**PRODUCT ID: 68196**  
**DOT LED Blank-Out Sign**

**MODEL**  
 DOT3535RW-A049/100-240VAC



**DIMENSIONS**  
 35" H x 35" W x 6.5" D (est. 76.675 lbs)

**CLASS**  
 Class: DOT Series  
 Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
 Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66.  
 Hinged door with silicone gasket, tool-less stainless-steel latches. 6.5" Deep.  
 Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109)  
 Faces: Single Faced Sign  
 Finish: Powdercoat Black

**ELECTRICAL**  
 Input Voltage: 100-240 VAC  
 Photodimming: IR photocells for auto photodimming  
 Power Supplies: Redundant  
 UL/cUL Listed: Listed for wet locations


**MESSAGE**  
 Illumination: Super bright direct view LEDs. Message blanks out when off.  
 Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
No Right Turn Symbol	Red, White Narrow Angle	26.25", 15.75"	0.259-0.108

NOTE: Above messages are independently controlled.

**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

