PRODUCT ID: 6891

Outdoor Blank-out LED Direct-view Sign

MODEL TCL1434GGR-652/120-277VAC



DIMENSIONS 14" H x 34" W x 2.5" D (est. 11.569 lbs)

CLASS

CLASS: TCL Series Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep. Face Material: 1/8" impact resistant, smoke-tinted polycarbonate (5109) Faces: Single Faced Sign Finish: Duranodic Bronze Mounting Channel: None

ELECTRICAL

Flashing: Not Included Input Voltage: 120-277 VAC Photodimming: None UL/CUL Listed: Listed for wet locations

MESSAGE

Illumination: Super bright direct view LEDs. Message blanks out when off. Sign Messages: See message table below

| _ | Product View | NOTE: Sign image may not exactly represent the finished product. For illustration purposes only. | | |
|----------------------------|--------------|--|-------------------------------------|--|
| | | | | |
| | | | | |
| | | | 14 in | |
| | ₹ | | <u>.</u> <u>∳</u> → → ↓ 1/2 in → | |
| S 52 24 18 | | Sample Display Options | | |
| Ì | B | USINESS LANE | Frame Detail | |

| MESSAGE | LED/COLOR | HEIGHT | AMPS |
|--------------------|-------------------------|-----------|-------------|
| BUSINESS LANE | Green Wide Angle LED | 3.5" | 0.144-0.062 |
| OPEN | Green Wide Angle LED | 3.5" | 0.055-0.024 |
| CLOSED | Red Wide Angle LED | 3.5" | 0.041-0.018 |
| NOTE: Above messag | es are independently co | ntrolled. | |
| | | | |
| | | | |