

CS-304U

WIDE RANGE WEATHERPROOF SPEAKER 30W



The CS-304 outdoor speaker features stainless steel hardware for all-weather durability. It is designed to offer the high intelligibility of weather-resistant horns combined with the high sound quality of dynamic speakers. The CS-304 employs the rotary switch that facilitates impedance changes. It also employs a constant directivity horn for clear sound output over its horizontal range of 90° operation.

Key features



- Ensure long-lasting outdoor performance with a rust-resistant stainless steel and resin construction.
- Deliver uniform sound coverage across your space through the 90-degree constant directivity horn.
- Maintain reliable operation in harsh weather conditions with certified IP65 dust and water protection.
- Save time during setup by easily adjusting power levels with the built-in rotary switch.
- Meet strict safety and professional standards with the UL 1480 listed design.
- Enhance facility safety using fire-retardant materials that meet UL94 V-0 standards.
- Enjoy flexible installation options on walls or ceilings with the included stainless steel bracket.

Specifications

Rated Input	30 W
Rated Impedance	100 V line: 330 Ω (30 W), 500 Ω (20 W), 1 k Ω (10 W) 70 V line: 170 Ω (30 W), 330 Ω (15 W), 500 Ω (10 W), 1 k Ω (5 W)
Sensitivity	98 dB (1 W, 1 m)
Frequency Response	120 Hz - 15 kHz
Horizontal Directivity	Constant directivity horn 90° ($\pm 45^\circ$ horizontal from front axis) 93 dB or more (1 W, 1 m), 3 kHz at $\pm 45^\circ$
Speaker Component	12 cm cone-type
Speaker Cable	2-core cabtyre cord with diameter of 6 mm
Compliance/Certifications	UL1480 (UEAY (outdoor use))
Dust/Water Protection	IP65
Finish	Horn, cover: Fire-resistant ABS resin (resin material grade: UL-94 V-0), off-white, paint Bracket: Stainless steel Net: Aluminum, gray, paint Screw: Stainless steel
Dimensions	366 (W) x 230 (H) x 272 (D) mm
Weight	3.1 kg

[Note] Do not install the speaker face-up from a horizontal plane nor in such a way that the paper cone is exposed to direct sunlight. If water accumulates on the paper cone, or ultraviolet rays are radiated on it, this may cause the paper cone to deteriorate, leading to speaker malfunction.

Dimensions



UNIT: mm

A&E specifications

The wide-range paging speaker shall be a constant-directivity design,. The speaker component shall be a 12 cm (4.72") cone-type driver, treated for weather resistance. Power handling shall be 30 W. The speaker shall incorporate a matching transformer for 70 V and 100 V distributed systems.

Transformer wattage taps shall include:

70 V: 30 W (170 ohms), 15 W (330 ohms), 10 W (500 ohms), 5 W (1k ohms);

100 V: 30 W (330 ohms), 20 W (500 ohms), 10 W (1k ohms).

Sensitivity (1 W/1 m) shall be 98 dB. Frequency response shall be 120 Hz – 15 kHz. Horizontal directivity shall be 90°. The paging speaker shall be UL Listed under category UL 1480 (UEAY). The speaker shall comply with IEC IP-65 for dust and moisture resistance. The horn and cover material shall be fire-resistant ABS resin, off-white, and painted. The protective net shall be aluminum with gray paint. All mounting hardware, including the bracket and screws, shall be stainless steel. Terminations shall be via an integral 2-core cabtyre cord, 6 mm (0.24") diameter and 600 mm (24") length. Dimensions (W × H × D) shall be 366 × 230 × 272 mm (14.41" × 9.06" × 10.71"). Weight shall be 3.1 kg (6.83 lb).

The wide-range paging speaker shall be TOA model CS#304U