

F-2352CU2

PANEL CONE SPEAKER



The F-2352CU2 ceiling-mounted speaker covers an extremely wide area and can be used for 25 and 70 V line applications. Well-balanced sound can be heard uniformly at any location.

Key features

- Ported bass-reflex design
- Co-axial: 5" cone driver and dome tweeter
- Special diffuser provides wide off-axis high frequency response
- Metal back-can and safety cable
- UL-Listed for General Purpose Signaling and Air-Handling Spaces (UL1480 UEAY, UL2043, CAN/CSA C22.2 No.205 (UEAY7)
- Removable terminal block with loop-through terminations
- Overload protection circuitry
- For medium ceiling height (2 to 4 m)

Specifications

Enclosure	Bass reflex type
Rated Input	30 W (High Impedance)
Power Handling	Continuous pink noise: 60 W (8 Ω) Continuous program: 120 W (8 Ω)
Impedance	70 V line: 170 Ω (30 W), 330 Ω (15 W), 1 kΩ (5 W), 3.3 kΩ (1.5 W), 10 kΩ (0.5 W) 25 V line: 170 Ω (3.7 W), 330 Ω (1.9 W), 1 kΩ (0.6 W), 3.3 kΩ (0.2 W), 10 kΩ (0.06 W) 8 Ω
Sensitivity	90 dB (1 W, 1 m)
Frequency Response	70 Hz - 20 kHz at installation in 1/2 free sound field (Measured by installing the unit in the center of a ceiling.)
Speaker Component	High frequency: Balanced dome-type Low frequency: 12 cm (5) cone-type
Mounting Hole	Ø200 mm (7.87) (Maximum ceiling thickness: 37 mm (1.46"))
Input Terminal	Removable locking connector with screw-down terminals (2 input terminals and 2 bridge terminals)
Cable Requirements	Solid copper wire: Ø1.0 - Ø1.6 mm (equivalent to AWG No. 18 - 14) Stranded copper wire: 0.75 - 2.5 mm ² (equivalent to AWG No. 18 - 14)
Compliance/Certifications	UL1480 (UEAY), UL2043, CAN/CSA C22.2 No.205 (UEAY7)
Finish	Enclosure: Steel plate, plating Baffle: Fire-resistant ABS resin (resin material grade: UL-94 V-0), black Rim: Fire-resistant ABS resin (resin material grade: UL-94 V-0), white, paint Punched net: Steel plate, white, paint
Dimensions	Ø230 x 238 (D) mm (Ø9.06 x 9.37")
Weight	4.3 kg (9.48 lb) (including mounting accessories)
Included Accessories	Front grille ...1, Tile bridge ...1, Safety wire (approx. 60 cm (23.62) ...1
Optional Accessories	Back can: HY-BC1, Trim ring: HY-TR1

Dimensions

