

## VX-3000CT AMQ

### CONTROL PANEL



The VX-3000CT is an operation panel designed for exclusive use with the VX-3000 Series. Operation such as the activation of general broadcast and the input/output volume control can be performed by connecting the VX-3000CT to the VX-3000 Frame via network. It is equipped with 9 function keys and 8 volume controls. Up to 2 units can be connected to a single VX-3000 Frame, and a maximum of 80 units can be configured per system.

### Key features

- Control panel with 9 function keys and 8 volume control knobs for easy operation
- Function keys are used for public address operation such as the activation of general broadcast.
- Volume controls allow volume level adjustment of the frame's audio input or audio output (assignable).
- Up to 2 units can be connected to a single frame unit.

## Specifications

Power Source	20 – 33 V DC, removable terminal block (4 pins)
Current Consumption	0.09 A at 33 V DC input, 0.11 A at 24 V DC input
LAN A, B	Number of Connectors: 2 (LAN A, LAN B)
Indicators	Power (Green) x 1, Run (Green) x 1, Link/ACT (Green) x 2, Signal (Green) x 8, Fault (Yellow) x 1, Status (Green/Yellow) x 9, Select (Green)x 9
Volume Control	8 channels
Operation	Function key x 9, Reset Key x 1, IP address setting switch x 1
Dimensions	482 x 44 x 315.2 mm
Weight	3 kg