

## KVM over IP Remote-User Console Station

MODEL NUMBER: **B064-000-STN**



Enterprise-level, Java-free user console station provides remote access to your Tripp Lite B064-IPG KVM switches.

### Features

**Monitor and Control Your KVM over IP Switches without a Computer** This enterprise-level user console station gives you remote access to your B064-IPG KVM switches without the use of a PC, laptop or notebook computer. With no operating system, you no longer have to worry about forced system or software updates. You're also protected against the threats of viruses, spam, phishing and malware by allowing access only to connected servers and not email, apps, malicious websites or any other Internet-based potential threats to your system. The Java-free platform lets you avoid certain access issues and security vulnerabilities.

**Preview up to 64 Servers at the Same Time with Panel Array Mode** Panel array mode lets you monitor and manage the video output from as many as 64 connected servers at the same time, all on one HDMI monitor. By previewing every connected server simultaneously, the B064-000-STN is ideal for network applications that require constant monitoring, such as surveillance and security. The HDMI port supports high-definition resolutions up to 1920 x 1200, including 1080p, at 60 Hz.

**Connect Storage Media to a Target Server Anywhere on the Network with Virtual Media** The Virtual Media feature allows a removable USB drive on a user's system to appear and act as if it were installed on the remote server. Up to two virtual media choices can be mounted. Once mounted, you can treat the virtual media as if they really exist on the remote server. Drag and drop files to or from them, open files on the remote server for editing and save them to the redirected media. The B064-000-STN features two USB 2.0 ports for peripherals, as well as inputs for a USB keyboard and mouse and two audio jacks.

**Designed for Flexible Placement and Installation** Four rubber feet are also included for resting the unit on a flat, level surface, such as a shelf, table or desk. You can also use the included mounting plate to install the console server on a wall or in a space-saving 0U rear-of-the-rack configuration. The B064-000-STN supports hot-plugging, which allows you to connect, disconnect, add or remove components without having to shut down the unit.

**Compatible with B064-IPG-Series IP KVM Switches** The B064-000-STN is designed to work with the following KVMs: B064-008-01-IPG, B064-016-01-IPG, B064-016-02-IPG, B064-016-04-IPG, B064-032-01-IPG, B064-032-02-IPG, B064-032-04-IPG and B064-064-08-IPG. It supports boundless switching when cascaded with another B064-000-STN console station via user-supplied Cat5e/6 cabling.

**TAA-Compliant for GSA Schedule Purchases** The B064-000-STN is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

### Highlights

- Replaces a PC or laptop, eliminating forced system updates and avoiding virus threats
- Monitors and manages video output of up to 64 servers simultaneously on one display
- Remotely connects storage media to a target server anywhere on the network
- Java-free platform avoids access issues and vulnerabilities of frequent manual updates
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

- Monitor and control Tripp Lite B064-IPG KVM switches from a remote centralized location

### System Requirements

- Works with B064-IPG KVMs, including B064-008-01-IPG, B064-016-01-IPG, B064-016-02-IPG, B064-016-04-IPG, B064-032-01-IPG, B064-032-02-IPG, B064-032-04-IPG and B064-064-08-IPG
- HDMI monitor
- USB keyboard/mouse
- Wired Ethernet network

### Package Includes

- B064-000-STN HDMI KVM over IP Remote-User Console Station
- (4) Rubber feet
- Mounting plate
- External power supply with 4 ft. cord and C13 to NEMA 5-15P input (Input: 100–240V, 50/60 Hz, 0.7A; Output: 5V 4A)
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

## Specifications

| OVERVIEW                                  |                                                     |
|-------------------------------------------|-----------------------------------------------------|
| UPC Code                                  | 037332252777                                        |
| Accessory Type                            | Remote Management                                   |
| Technology                                | Cat6; HDMI; Stereo Audio; USB 2.0 (High Speed)      |
| Accessory Class                           | KVM Switch Accessories                              |
| VIDEO                                     |                                                     |
| Max Supported Video Resolution            | 1920 x 1200 @60Hz                                   |
| AUDIO                                     |                                                     |
| Audio Specification                       | Stereo Audio                                        |
| INPUT                                     |                                                     |
| AC Power Adapter Plug(s)                  | NEMA 5-15P North America                            |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.7A                           |
| AC Power Adapter Output Specs (V / A)     | 5V / 4A                                             |
| AC Power Adapter Cord Length (ft.)        | 4                                                   |
| AC Power Adapter Cord Length (m)          | 1.2                                                 |
| Voltage Compatibility (VAC)               | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240    |
| Redundancy - Dual Power Inputs            | No                                                  |
| POWER                                     |                                                     |
| Power Source Type                         | AC Adapter                                          |
| DC Barrel Plug                            | OD: 5.5 x 2.5 x 12mm, Positive Pin, Negative Sleeve |
| Power Consumption (Watts)                 | 4.66                                                |
| Power Consumption Detail                  | DC: 5V (4.66W)                                      |
| CONNECTIONS                               |                                                     |
| Side A - Connector 1                      | DB9 (FEMALE); RJ45 (FEMALE); (4) USB A (FEMALE)     |
| Side B - Connector 1                      | (2) 3.5MM (FEMALE); HDMI (FEMALE); RJ45 (FEMALE)    |
| Console Keyboard and Mouse Interface      | USB                                                 |
| Console Monitor Interface                 | HDMI                                                |
| USER INTERFACE, ALERTS & CONTROLS         |                                                     |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                              |
|--------------------------------------|------------------------------|
| LED Indicators                       | Power (Blue)                 |
| <b>PHYSICAL</b>                      |                              |
| Color                                | Black                        |
| Material of Construction             | Metal                        |
| Rackmountable                        | Yes                          |
| Shipping Dimensions (hwd / in.)      | 8.27 x 3.86 x 12.80          |
| Shipping Dimensions (hwd / cm)       | 21.01 x 9.80 x 32.51         |
| Shipping Weight (lbs.)               | 3.09                         |
| Shipping Weight (kg)                 | 1.40                         |
| Unit Dimensions (hwd / in.)          | 6.860 x 5.880 x 1.130        |
| Unit Packaging Type                  | Box                          |
| Unit Weight (lbs.)                   | 1.65                         |
| Unit Weight (kg)                     | 0.75                         |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 32° to 104°F (0° to 40°C)    |
| Storage Temperature Range            | -4° to 140°F (-20° to 60°C)  |
| Relative Humidity                    | 0% to 80% RH, Non-Condensing |
| <b>COMMUNICATIONS</b>                |                              |
| Network Compatibility                | 1 Gbps (Gigabit)             |
| <b>PORT EXPANSION</b>                |                              |
| Daisy-chainable or Cascadable        | Cascadable                   |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| USB Hub Ports                        | Yes                          |
| Number of USB Hub Ports              | 2                            |
| USB Specification                    | USB 2.0 (up to 480 Mbps)     |
| On-Screen Display (OSD)              | No                           |
| Port Selection                       | GUI                          |
| HDCP Specification                   | 1.4                          |
| Driver Required                      | No                           |
| Recommended Category Cable           | N201-Series Cat6 Cables      |
| <b>REMOTE ACCESS</b>                 |                              |
| Modem Port                           | Yes                          |

| STANDARDS & COMPLIANCE               |                                                    |
|--------------------------------------|----------------------------------------------------|
| External Power Supply Certifications | CCC; CE; FCC; PSE; TUV; UL; cUL                    |
| Product Compliance                   | RoHS; REACH; FCC (USA); Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT                   |                                                    |
| Product Warranty Period (Worldwide)  | 3-year limited warranty                            |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.