

5.5kW Single-Phase Local Metered PDU, 208/230V Outlets (16 C13 & 2 C19), L6-30P, 12 ft. (3.66 m) Cord, 2U Rack-Mount, TAA

MODEL NUMBER: PDUMH30HV



Highlights

- Local metered single phase 24A 208/230V 2U horizontal rackmount PDU
- Two built-in meters report output current in amps for each load bank
- Attached 12-ft. (3.66 m) cord with NEMA L6-30P input plug
- 18 total outlets (16 C13, 2 C19)
- Reversible housing, 2U 208/230V rackmount local metered PDU
- TAA Compliant

Package Includes

- 2U rack PDU
- Mounting brackets
- Plug retention plates
- User manual

Features

- 30A single phase 208/230V Local Metered Power Distribution Unit / rack PDU (rPDU) (Agency derated to 24A continuous)
- Set of two lighted meters report PDU output current in amps for each 9 outlet load bank
- Attached NEMA L6-30P 30A 208/230V input plug and 12-ft. (3.66 m) cord
- 2U horizontal rackmount format installs in two rack spaces
- 18 output receptacles (16 C13, 2 C19)
- Outlets are arranged in two 9 outlet load banks, each with separate 20A breaker and current metering
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Cord retention brackets keep vital equipment plugs connected
- Grounding lug
- Compliant with the Federal Trade Agreements Act(TAA) for GSA Schedule purchases

Specifications

| OVERVIEW | |
|-------------------|---------------|
| UPC Code | 037332159021 |
| PDU Type | Local Metered |
| INPUT | |
| Input Phase | Single-Phase |
| PDU Input Voltage | 208; 230 |



Powering Business Worldwide



| | |
|--|---|
| Recommended Electrical Service | Single-phase 30A 208/230V service |
| Maximum Input Amps | 24 |
| Maximum Input Amps Details | Agency de-rated to 24A continuous |
| PDU Plug Type | NEMA L6-30P |
| Input Cord Length (ft.) | 12 |
| Input Cord Length (m) | 3.66 |
| OUTPUT | |
| Output Capacity Details | 5.5kW (230V), 5kW (208V) total capacity / 30A max (Agency de-rated to 24A), 20A max per breaker outlet bank; 16A max per C19 outlet; 12A max per C13 outlet |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (16) C13; (2) C19 |
| Output Nominal Voltage | 208/230V |
| Overload Protection | Two 20A breakers protect 9 outlets each |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LCD Display | Set of 2 digital meters continuously report output current for breaker outlet banks 1 & 2 (Bank 1: upper row of 9 outlets / Bank 2: lower row of 9 outlets) |
| SURGE / NOISE SUPPRESSION | |
| Automatic Shut-Off | No |
| PHYSICAL | |
| Material of Construction | Metal |
| Rack Height | 2U |
| Form Factors Supported | 2U rackmount; mounting accessories included |
| Minimum Required Rack Depth (cm) | 40.64 |
| Minimum Required Rack Depth (inches) | 16 |
| PDU Form Factor | Horizontal (2U) |
| Shipping Dimensions (hwd / in.) | 7.80 x 16.70 x 19.80 |
| Shipping Dimensions (hwd / cm) | 19.81 x 42.42 x 50.29 |
| Shipping Weight (lbs.) | 15.80 |
| Shipping Weight (kg) | 7.17 |
| Unit Dimensions (hwd / in.) | 3.500 x 17.500 x 12.500 |
| Unit Dimensions (hwd / cm) | 8.8 x 44.4 x 31.8 |
| Unit Weight (lbs.) | 13.7 |
| Unit Weight (kg) | 6.21 |
| ENVIRONMENTAL | |



Powering Business Worldwide



| | |
|--------------------------------------|---|
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Storage Temperature Range | -22° to 122°F (-30° to 50°C) |
| Relative Humidity | 5% to 95% non-condensing |
| Operating Elevation | 0-10000 ft. (0-3000 m) |
| FEATURES & SPECIFICATIONS | |
| Grounding | Grounding lug |
| STANDARDS & COMPLIANCE | |
| Product Certifications | NOM (Mexico); UL 62368-1 |
| Product Compliance | RoHS; FCC Part 15 Class A (USA); UKCA; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.