

UPS Battery Replacement for Select SMART1200LCD, SMART1500LCD, SMART1500LCDXL, SMX1500LCD UPS Systems

MODEL NUMBER: RBC1500



UPS backup battery replacement breathes new life into select Tripp Lite UPS systems whose internal batteries are expired or weak.

Features

UPS Replacement Battery Cartridge for Select UPS Systems This UPS backup battery replacement is compatible with SMART1200LCD, SMART1500LCD, SMART1500LCDXL and SMX1500LCD UPS systems—the versions equipped with battery access doors only. Earlier versions of these models without a battery door are not compatible with the RBC1500. Please verify UPS compatibility as labeled on the UPS prior to ordering.

Carefully Screened and Certified Built to function in a wide range of operating temperatures, the RBC1500 has been carefully screened and certified to restore your UPS system’s runtime performance to its original specifications.

Ready for Immediate Installation The leakproof, no-maintenance RBC1500 comes pre-assembled and pre-wired for quick and easy installation in your UPS system with battery access door. Reusable packaging holds expired batteries for delivery to the nearest recycling center.

Specifications

| OVERVIEW | |
|--------------------------|-------------------------------------------------------------|
| UPC Code | 037332214706 |
| BATTERY | |
| DC System Voltage (VDC) | 24 |
| Included Battery Set | Contains (2) 12V 9AH sealed lead acid batteries |
| Typical Battery Lifespan | 3 to 5 years typical, depending on UPS operating conditions |

Highlights

- Replacement battery backup for select battery-door-equipped UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery requires no regular maintenance
- Ships fully assembled and ready for immediate installation to prevent downtime
- Reusable packaging allows you to easily send expired batteries to recycling center

Applications

- Replace the aging or expired internal battery in your Tripp Lite battery-door-equipped UPS system

System Requirements

- SMART1200LCD, SMART1500LCD, SMART1500LCDXL and SMX1500LCD UPS system equipped with battery access door

Package Includes

- RBC1500 UPS Battery Replacement (pre-assembled battery pack with 2 12V batteries)



Powering Business Worldwide



| PHYSICAL | |
|-----------------------------------------|---------------------------|
| Shipping Dimensions (hwd / in.) | 6.50 x 8.07 x 12.60 |
| Shipping Weight (kg) | 6.53 |
| Unit Dimensions (hwd / in.) | 2.640 x 6.020 x 7.910 |
| Unit Dimensions (hwd / cm) | 6.71 x 15.29 x 20.09 |
| Unit Weight (lbs.) | 11.75 |
| Unit Weight (kg) | 5.33 |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (U.S. & Canada) | 18-month limited warranty |
| Product Warranty Period (International) | 1-year limited warranty |
| Product Warranty Period (Mexico) | 1-year limited warranty |
| Product Warranty Period (Puerto Rico) | 1-year limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.