

3 Relay I/O Mini-module

MODEL NUMBER: RELAYIOMINI



Highlights

- Internal contact closure management accessory card
- Three relay output contacts
- Input signal to shutdown UPS

Package Includes

- RELAYIOMINI
- Owner's Manual

Description

The RELAYIOMINI allows users to communicate UPS status and events via three contact closure outputs. Installs in the back panel of compatible power modules on select SmartOnline® UPS systems only. Requires removal of USB module to install.

NOTE: Compatible with SmartOnline® UPS systems specifying the use of this accessory from 5 to 20kVA originally shipping with preinstalled back-panel USB module and dedicated RS-232 DB9 port. Compatible models: SU5000RT4UHV, SU5000RT4UTF, SU6000RT4U, SU6000RT4UHV, SU6000RT4UHVH, SU6000RT4UTF, SU6000RT4UTFH, SU8000RT3U, SU8000RT3UG, SU8000RT3UHW, SU8000RT3U1TF, SU8000RT3UN50, SU8000RT3UN50TF, SU10000RT3U, SU10000RT3UG, SU10KRT3U, SU10KRT3UHV, SU10000RT3U2TF, SU12KRT4UHW, SU16KRT, SU16KRT-1TF, SU16KRTG, SU16KRTHW, SU20KRT, SU20KRT-1TF, SU20KRTG, SU20KRTHW.

Features

- Makes select SmartOnline UPS capable of providing contact closure output communications
- 3 relay output contacts

Specifications

OVERVIEW	
UPC Code	037332155863
Accessory Type	Relay I/O Card
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.60 x 6.00 x 6.00
Shipping Dimensions (hwd / cm)	4.06 x 15.24 x 15.24
Shipping Weight (lbs.)	0.50
Shipping Weight (kg)	0.23
Unit Dimensions (hwd / in.)	0.910 x 2.360 x 2.790

Unit Dimensions (hwd / cm)	2.3 x 6.1 x 7.1
Unit Weight (lbs.)	.08
Unit Weight (kg)	0.04
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.