

Industrial 7-Port USB-C Hub, USB 3.x Gen 2 (10Gbps), 4x USB-A & 3x USB-C Ports, 15Kv ESD Immunity, 2Kv Surge

MODEL NUMBER: U460-4A3C-IND



Rugged industrial hub adds 4 USB-A and 3 USB-C ports to a USB-C computer for connecting industrial printers, sensors and other USB devices.

Features

Industrial-Grade USB 3.1 Gen 2 Hub Adds up to 7 USB Devices to Your Computer This USB 3.1 Gen 2 hub with a heavy-duty all-metal housing connects as many as seven USB devices, such as external hard drives, industrial printers, barcode scanners, serial devices and sensors, to your host computer. The heavy-duty metal housing withstands harsh physical conditions in industrial and commercial locations, such as factories, construction sites, supply rooms and warehouses. **Note:** Host must support USB OTG (On-the-Go) **Transfers Data at Super-Fast USB 3.1 Gen 2 Speeds and Charges Mobile Devices**

The four USB-A and three USB-C ports can transfer data at speeds up to 10 Gbps, which is twice as fast as USB 3.1 Gen 1. If all the ports are used simultaneously, each port provides up to 0.9 amps of power. Because the ports are BC 1.2-compliant, they can deliver up to 1.5 amps of charging power to mobile devices (when connected to power). The ports are backward compatible with previous USB generations, so you can continue using older peripherals while getting high-speed performance from new devices.

USB-C Ports Support Cables with Locking Screws for Extra-Secure Connections Equipment vibrations in industrial environments can loosen cable connections over time. This hub's USB-C ports, including the host port, support USB cables that have locking screws to help prevent unintentional disconnection. The hub comes with a 2 ft. USB-C cable with male connectors; one connector has locking screws for secure attachment to the hub's host port. The other end connects to your computer.

Protects Your Devices Against Electrostatic Discharge (ESD) and Overcurrent Machines on the shop floor can generate electrostatic discharges, which can wipe out data and damage sensitive electronics. This seven-port hub includes ESD protection to ± 15 kV, reducing potential static damage to connected peripherals. This feature works in tandem with ± 2.5 kV per port overcurrent protection to safeguard connected devices against damage and data loss from power surges.

Plug-and-Play Hub Offers Flexible Power and Mounting Options This hub does not require software or drivers. To power the hub, use the included 2-wire terminal block to draw power from a power terminal or connect a compatible user-supplied power adapter to an AC outlet. LEDs indicate power and connection status. Place the hub on a flat surface or mount it to a wall or desk using the built-in brackets and user-supplied hardware.

TAA-Compliant for GSA Schedule Purchases The U460-4A3C-IND complies with the Federal Trade

Highlights

- Adds barcode scanner, serial device, sensor—up to 7 devices—to your host computer
- Supports USB 3.1 Gen 2 rates up to 10 Gbps to ensure super-fast data transfers
- ESD protection to ± 15 kV helps prevent potential static damage to connected devices
- Rugged metal housing withstands warehouse and factory environments
- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Applications

- Connect up to 7 USB devices and peripherals to your computer or laptop
- Add easy-to-access USB ports to computers stored in a cabinet, behind furniture or other hard-to-reach location
- Mount to a wall or DIN rail in a harsh environment, such as a factory, construction site, supply room or warehouse

System Requirements

- Compatible with all USB-enabled operating systems (USB 3.1 Gen 2 port needed to achieve USB 3.1 Gen 2 speeds)

Package Includes

- U460-4A3C-IND 7-Port Industrial-Grade USB 3.1 Gen 2 Hub
- USB 3.1 Gen 2 Type-C cable, 2 ft.
- 2-wire terminal block
- Owner's manual



Powering Business Worldwide



Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

| OVERVIEW | |
|-----------------------------------|--|
| UPC Code | 037332239914 |
| Product Type | Hub |
| Technology | USB 3.x |
| Host Connector | USB C (MALE) |
| VIDEO | |
| Number of Monitors Supported | 0 |
| Extended Mode | No |
| Mirror Mode | No |
| DATA | |
| Data Ports | (4) USB A (FEMALE); (3) USB C (FEMALE) |
| Data Ports Details | (4) USB-A - USB 3.2 Gen 2 (10 Gbps); (3) USB-C - USB 3.2 Gen 2 (10 Gbps) |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240 |
| Voltage Compatibility (VDC) | 12-24 |
| Bus Powered | No |
| BATTERY | |
| Battery Charging (5V/1.5A Port) | Yes |
| POWER | |
| DC Barrel Plug | OD: 5.5 x 2.5 x 9.5mm, Positive Pin, Negative Sleeve |
| CONNECTIONS | |
| Number of Ports | 7 |
| Side A - Connector 1 | USB C (FEMALE) |
| Side B - Connector 1 | (4) USB 3.1 A (FEMALE) |
| Side B - Connector 2 | (3) USB C (FEMALE) |
| Connector Plating | Nickel |
| USER INTERFACE, ALERTS & CONTROLS | |

| | |
|--------------------------------------|---|
| LED Indicators | x1 Power (Blue) and x7 device activity (Green) |
| CHARGING | |
| Total Charging Watts | 7.5 |
| Charging Ports / Amps | (7) 1.5A |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Steel |
| Housing Color | Black |
| Shipping Dimensions (hwd / in.) | 2.48 x 9.06 x 7.80 |
| Unit Dimensions (hwd / in.) | 0.800 x 7.400 x 2.500 |
| Unit Dimensions (hwd / cm) | 2 x 18,8 x 6,4 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.67 |
| Unit Weight (kg) | 0.30 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 122°F (0° to 50°C) |
| Storage Temperature Range | 14° to 176°F (-10° to 80°C) |
| Relative Humidity | 0% to 90% RH, Non-Condensing |
| BTUs | 10.23 BTU/hr |
| FEATURES & SPECIFICATIONS | |
| Over Current Protection | Yes |
| USB Hub Ports | Yes |
| Number of USB Hub Ports | 7 |
| USB Specification | USB 3.2 Gen 2 (Up to 10 Gbps) |
| UASP Support | Yes |
| Driver Required | No |
| STANDARDS & COMPLIANCE | |
| Product Compliance | RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |



Powering Business Worldwide



1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.