GMP252 CO2 Probe for ppm Measurements

Type	Options	1	2	3	4	5	6	7	8
Probe Type	0...10 000 ppm Probe with Sintered PTFE Filter	1							
	0...5000 ppm Probe with Sintered PTFE Filter	2							
	0...2000 ppm Probe with Sintered PTFE Filter	3							
	0...3000 ppm Probe with Sintered PTFE Filter	4							
	0...20 000 ppm Probe with Sintered PTFE Filter	5							
	0...20 000 ppm Probe with Porous Sintered PTFE Filter (Indigo80)	6							
	0...30 000 ppm Probe with Sintered PTFE Filter	7							
Output Mode	RS-485 Modbus		0						
	RS485		1						
	4...20mA Output		2						
	0...20mA Output		3						
	0...5V Output		4						
	0...10V Output		5						
	0...1V Output		6						
	0...10V Output with Error Level 10.3V		A						
Temperature Compensation	Temperature Setpoint +25°C (+77°F)			A					
	Temperature Setpoint +37°C (+99°F)			B					
	Active Internal Temperature Compensation ON			C					
Pressure Compensation	Pressure Setpoint 1013 hPa				0				
	Pressure Setpoint 982 hPa				T				
Background Gas Compensation	Background Gas Setpoint 0%O2, 0%RH					A			
	Background Gas Setpoint 21%O2, 50%RH					B			
Cable	No Cable						0		
	1.5 m Probe Cable with Open Wires						1		
	0.6 m Probe cable with Open Wires and 90° Plug						3		
	10 m Probe Cable with Open Wires						4		
	3 m Probe Cable with Open Wires						5		
	1.5 m Probe cable with Open Wires and 90° Plug						6		
	High Temperature Durable Cable With Open Wires						7		
	M12-M12 Probe Connection Cable (Indigo80)						8		
	Flat Probe Connection Cable (Indigo80)						9		
Mounting	Probe Mounting Clips (2 pcs)							C	
	Probe Mounting Flange							F	
	Probe Handle with Magnetic Hanger (Indigo80)							H	
	No Mounting Accessories							N	
Package	Single Package								1
	10 Piece Multi-package (available if the order contains 10 units)								2
	Single Package for Probe with Handle (Indigo80)								3