TMT120 Temperature Transmitter, +/-0.1 degC (+/-0.18 degF), 4...20 mA

Type	Options	1	2	3	4	5	6	7	8	9	10	11	12	13
Measurement Type	Temperature, HMP110T Stainless Steel Probe	A												
	TMP115 3m, with 5-point calibration -90, -45, 0, +45, +90 °C	B												
	TMP115 3m, with 6-point calibration -196,-90,-45, 0, +45,+90 °C	C												
Probe Details	Probe Mounted on Transmitter (Stainless Steel Probe)		A											
	3 m Cable for Remote Probe		B											
	5 m Cable for Remote Probe		C											
	10 m Cable for Remote Probe		D											
	10 m with Cable for Remote Probe with 10m Extension Cable		E											
	20 m Cable for Remote Probe		F											
	1,2 m Remote Probe Cable		G											
	TMP115 Mounted on Transmitter		M											
Display	No Display			0										
	With Display			1										
	No Display, No Logo (HMT120)			N										
Output Signal	Output 4...20mA, 2-wire loop-powered				A									
Parameter for Output 1	T -40...+60 °C (-40...+140 °F)					B								
	T -20...+80 °C (-4...+176 °F)					C								
	T 0...+60 °C (+32...+140 °F)					D								
	Temperature Range T -40...+80 °C (-40...+176°F)					E								
	Temperature Range T 0...+50 °C (+32...+122°F)					F								
	Temperature Range T -90 … 0 C (-130...+ 32°F)					G								
	Temperature Range T -90 … +30 C (-130...+ 86°F)					H								
	Temperature Range T -200 … +0 C (-328...+ 32°F)					J								
	Channel 1 Parameter and Custom Scaling					X								
Parameter for Output 2	Channel 2 No Output						A							
Display Units	Metric Units							1						
	Non Metric Units							2						
Sensor Protection	Plastic Grid for Steel Probe								1					
	Plastic Grid with PTFE filter for Steel Probe								2					
	Stainless steel sintered filter								3					
	Sintered Teflon Filter for Steel Probe								E					
	TMP115 sensor								N					
Transmitter Installation	No Accessories									A				
	Rain Shield with Installation Kit									C				
Installation Kit for Probe	No Accessories										1			
	Duct Installation Kit										2			
	Probe Mounting Flange										3			
	Solar Radiation Shield with Probe Installation Kit										5			
	Probe Mounting Clamp										6			
	Magnetic probe holder										7			
Cable Bushings	Cable Gland for 2...6 mm Diameter Cable											A		
	Conduit Fitting PG9											B		
	Conduit Fitting NPT 1/2"											C		
	No Bushing (with rubber plug)											D		
	All Bushings (Includes Cable Gland, PG9 and NPT1/2" Conduit Fittings)											Z		
PC Accessories	No Accessories												0	
	USB Service Cable for PC												1	
Operation Manual Language	No User's Guide													A
	Multilingual Manual													Z