TMW90 Room Temperature Transmitter, Wall Mounted

Type	Options	1	2	3	4	5	6	7	8	9
Output	2-wire current output	2								
	3-wire voltage output	3								
Output signal	4...20 mA 2-wire (loop-powered)		1							
	0...10 V 3-wire		2							
	0...5 V 3-wire		3							
Output scaling for temperature	T -5 ... +55 °C (+23 ...+131°F)			A						
	T -0 ... +60 °C (+32 ...+140 °F)			B						
	Special scale please specify:			X						
Display and color	Solid Cover White RAL9003 (hidden display)				0					
	Display Cover White RAL9003 (visible display)				1					
	Solid Cover Black RAL9005 (hidden display)				2					
	Display Cover Black RAL9005 (visible display)				3					
	Solid Cover White RAL9003, no logo (hidden display)				8					
	Display Cover White RAL9003, no logo (visible display)				9					
Units	Metric units					A				
	Non metric units					B				
Relay operation	None						0			
	Relay open below setpoint						1			
	Relay open above setpoint						2			
	Relay closed in error state						F			
	Relay closed in normal operation						N			
Relay set-point and hysteresis	None							0		
	T setpoint (low/high):							X		
Identity	With adjustment trimmers								A	
	No adjustment trimmers								B	
Quick reference guide	No User's Guide									0
	Multilingual Quick Guide for Analog HMW90/GMW90 Series Devices									2