PRO CLEAN™

High Strength Natural Solvent

PRO CLEAN™ is an innovation in environmentally friendly cleaning technology. PRO CLEAN™ is powerful and fast acting cleaner of the most extreme contaminants such as paint, ink, adhesives, anti-corrosion waxes, resins and even tar. PRO CLEAN™ can even be used to remove grease, oil, lubricants, fat and other traditional organic contaminants. Formulated with a proprietary blend of bio-renewable vegetable-based extracts (Nature Boost™), it is low VOC, has a high flash point (102°C/215° F) and is readily biodegradable. PRO CLEAN™ is the perfect alternative to solvent-based and d-limonene-based cleaners.

Features & Benefits:



- Powerful alternative to traditional solvent and d-limonene-based cleaners
- Unique blend of vegetable-based extracts providing high solvency for fast and easy removal of difficult-to-remove contaminants
- Formulated to remove paint, ink, adhesives, anti-corrosion waxes, tar, sealant, grease, oils, lubricants and fat.
- Can be used in spray applications for manual cleaning operations and immersion bath applications for cleaning complex geometrical parts.
- Ensures complete evaporation after wiping.
- Slow evaporation
    - o Longer application time possible
    - o Less consumption (i.e. economical)
- Safe on all metals and most plastics.
- Free of chlorinated solvents, petroleum distillates and d-limonene.
- Non-corrosive
- Ready to use formulation, no dilution required.

Nature Boost

Description	Size		Order No.	MSDS
	Metric	Imperial		
Trigger Sprayer	500mL	16.9 oz.	53-G 523	L-169E
Liquid	3.78L	1 gal.	53-G 525	L-169E
Liquid	20L	5.2 gal.	53-G 527	L-169E
Liquid	208L	55 gal.	53-G 528	L-169E

ACCESSORIES

Industrial pump sprayer	53-L 101
Spout for 20L pail	53-L 207
Faucet for 208L drum, 3/4"	53-L 209
Replacements trigger sprayer 500 mL	53-L 341
Bio-Circle® Clean Box Dip™	55-D 010

Technical Information

Density	0.89 g/ml at (20°C)
Color/Odor	Transparent / Slight
Flashpoint point	102°C (215°F)
pH	N/A
Solubility	Insoluble
VOC	19%

MSDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice

Walter Surface Technologies Inc.
5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1
Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825

Version 05 December 2025